



ENGLISH

Datasheet

Stock No. 123-3257

RS PRO IPM 243F Power Clampmeter



Feature:

- 10000 Count digital display
- Active Backlit, Large scale display
- VoltSense (None Contact Voltage)
- Analog Bar graph
- True RMS reading on AC and AC+DC mode
- Torch lightening when clamping
- Auto AC/DC 600 Amps capability and selection
- AC Current via Flexible Current Probe
- Auto AC/DC 1000 Volts capability and selection
- Auto Ohms/Continuity/Diode selection
- 100K Ohms Resistance capability
- Continuity Beeper
- Frequency Counter
- Power and Power factor measurement
- Total Harmonics distortion and Harmonics 1 to 25
- Capacitance capability
- Inrush Current
- DCA Auto-Zeroing Key
- Peak Hold
- MIN/MAX HOLD
- Smart Data Hold
- Phase rotation indication
- Low pass Filter
- Auto Power Off
- 4 feet Drop Proof
- Deluxe Carrying Case
- Convenient Battery Door
- CAT IV 600V / CAT III 1000V Safety Standard

Specifications:(All at 23°C ±5°C, ≤80% R.H.)

Voltage:

Function	Range	Accuracy*
DCV	99.99V	±(0.7% + 2dgt)
	999.9V	
ACV	99.99V	±(1.0% + 5dgt)
	999.9V	50 ~ 500Hz
HFR	99.99V	50 ~ 60Hz ±(1% + 5dgt)
ACV	999.9V	>60 ~ 400Hz ±(5% + 5dgt)

* DCV <1000dgt, add 6 dgt to the accuracy.

ACV <1000dgt, add 3 dgt to the accuracy.

Overload protection: 1000V_{rms}

Input Impedance: 3.5MΩ // <100pF

AC Conversion Type: AC Conversions are ac-coupled, true RMS responding, calibrated to the RMS value of a sine wave input. Accuracies are given for sine wave at full scale and non-sine wave below half scale. For non-sine wave (50/60Hz) add the following Crest Factor corrections:

For Crest Factor of 1.4 to 2.0, add 1.0% to accuracy.

For Crest Factor of 2.0 to 2.5, add 2.5% to accuracy.

For Crest Factor of 2.5 to 3.0, add 4.0% to accuracy.

CF 3 @ 460V, 280A

2 @ 690V, 420A

AC+DC V_{rms} Accuracy: same as ACV spec. +DCV spec.

Current:

Function	Range	Accuracy
DCA	99.99A	± (1.5% + 0.2A)
	599.9A	± (1.5% + 5dgt) **
ACA	0.10A ~ 99.99A	50 ~ 60Hz ± (1.5% + 5dgt) **
	599.9A	>60 ~ 400Hz ± (2% + 5dgt) **
HFR	0.10A ~ 99.99A	50 ~ 60Hz ± (1.5% + 5dgt) **
		>60 ~ 400Hz ± (5% + 5dgt) **
ACA	599.9A	>60 ~ 400Hz ± (5% + 5dgt) **

** The measured value <1000dgt, add 5 dgt to the accuracy.

Overload protection: 600A_{rms}

Position Error: ±1% of reading.

AC Conversion Type and additional accuracy is same as AC Voltage.

AC+DC A_{rms} Accuracy: Same as ACA spec + DCA spec.

— DCA affected by the temperature and the residual magnetism. Press HOLD key > 2sec to compensate it.

Peak Hold: Peak MAX / Peak MIN

Function	Range	Accuracy
ACV	140.0V	$\pm (3.0\% + 15\text{dgt})$
	1400V	
ACA	140.0A	$\pm (3.0\% + 15\text{dgt})$
	850A	

Overload protection: 1000 V_{rms}, 600 Arms

Accuracy defined for:

Sine wave, ACV>5Vrms / ACA \geq 5Arms, Freq.50~400Hz.

– Only suitable for the repetitive events.

Frequency:

Function	Range	Accuracy
Frequency	20.00 ~ 99.99Hz	$\pm (0.5\% + 3\text{dgt})$
	20.0 ~ 999.9Hz	
	0.020 ~ 9.999KHz	

Overload protection: 1000 V_{rms}, 600 A_{rms}

Sensitivity:

10~100Vrms for AC 100V range

10~100Arms for AC 100A range (>400Hz Unspecified)

100~1000Vrms for AC 1000V range

100~600/1000Arms for AC 600A/1000A range (>400Hz Unspecified)

- Reading will be 0.0 for signals below 10.0 Hz.

Total Harmonic Distortion:

Function	Range	Accuracy
ACA/ACV	99.9%	$\pm (3.0\% + 10\text{dgt})$

Harmonic distortion measurement:

Harmonic order	Range	Accuracy
H01 ~ H12	99.9%	$\pm (5\% + 10\text{dgt})$
H13 ~ H25		$\pm (10\% + 10\text{dgt})$

Overload protection: 1000 V_{rms}, 600 A_{rms}

– If ACV<10Vrms or ACA <10Arms, it will display “rdy”.

– If the fundamental frequency out of range 45 ~ 65Hz, it will display “out.F”.

Inrush Current:

Function	Range	Accuracy
ACA	99.99A	$\pm (2.5\% + 0.2A)$
	599.9A	$\pm (2.5\% + 5dgt)$

Overload protection: 1000 V_{rms}, 600 A_{rms}

Accuracy defined for:

Sine wave, ACA \geq 10Arms, Freq. 50/60Hz

- Integration time about 100ms

Active Power: Watt (DC/AC)

Function	Range	Accuracy
ACW / DCW	9.999 kW**	A,error×V,reading+ V,error×A,reading
	99.99 kW	
	599.9KW	

** The measured value < 1.000kW , add 10 dgt to the accuracy.

Overload protection: 1000 V_{rms}, 600 A_{rms}

Accuracy defined for:

ACW: Sine wave , ACV \geq 10 V_{rms}, ACA \geq 5 Arms Freq. 50~60Hz, PF=1.00

DCW: DCV \geq 10V , DCA \geq 5 A

Power Factor:

Function	Range	Accuracy*
PF	1.00	$\pm 5dgt$

Overload protection: 1000 V_{rms}, 600 A_{rms}

Resistance & Continuity & Diode:

Function	Range	Accuracy
Resistance	999.9 Ω	$\pm (1.0\% + 5dgt)$
	9.999 k Ω	$\pm (1.0\% + 3dgt)$
	99.99 k Ω	
Continuity	999.9 Ω	$\pm (1.0\% + 5dgt)$
Diode	0.40~ 0.80V	$\pm 0.1V$

Overload protection: 1000V_{rms}

Max. Test Current: Approx. 0.5mA

Maximum Open Circuit Voltage for Ω , Continuity: Approximate 3V

Maximum Open Circuit Voltage for diode: Approximate $\pm 1.8V$

Continuity Threshold : < 30 Ω Beep ON, > 100 Ω Beep OFF

Continuity Indicator: 2 KHz Tone Buzzer

Continuity response time: < 100ms

Capacitance:

Function	Range	Accuracy
Capacitance	3.999 μ F	$\pm (1.9\% + 8\text{dgt})$
	39.99 μ F	
	399.9 μ F	
	3999 μ F	

Overload protection : 1000 V_{rms}

Flex AC Current (voltage input):

Function	Range(1mV/1A)	Accuracy*
ACA	300.0A/3000A	1%+5dgt (50~500Hz) **
HFR ACA	300.0A/3000A	1%+5dgt(50~60Hz) ** 5%+5dgt(61~400Hz) **
Peak	420.0A/4200A	3%+80dgt(50~500Hz)
INRUSH	300.0A/3000A	2%+10dgt(50/60Hz)
Frequency	99.99Hz/999.9Hz	0.5%+3dgt(<500Hz)
THD	99.9%	5%+10dgt
Harm H01-H12	99.9%	5%+10dgt


*The accuracy of ICA 10T/18T is not included.

**ACA <300dgt, add 3 dgt to the accuracy.

Overload protection: 1000 V_{rms}

Trigger level of INRUSH: 1% of current range

General:

Sampling Rate:	3 times/sec
Overload Indication:	"OL" or "-OL"
Low Battery Indication:	
Auto Power Off:	Approx. 15 minutes after last operation
Operating Temperature:	0 °C ~ 30 °C ($\leq 80\%$ RH) 30 °C ~ 40 °C ($\leq 75\%$ RH) 40 °C ~ 50 °C ($\leq 45\%$ RH)
Storage Temperature:	-10°C to 50°C, 0% RH to 80% RH (batteries not fitted)
Temperature Coefficient:	0.2 x (Specified accuracy) / °C, < 18°C, > 28°C .
Safety:	IEC 61010-1: CAT IV 600V, CAT III 1000V
Maximum Conductor Size	37mm
Bus Bar Size	45mm x 10mm
Power Requirement:	9V Battery x 1
Battery Life: (Alkaline)	50 hours (without Backlight)
Size:	87.5mm(W) x 242mm(L) x 50.5mm(D)
Weight:	Approx. 435g (with battery)
Accessories:	Battery (installed), Carrying case, User Manual